

GAS HOT BOX (LARGE)

OLYMPIC

Party Hire

WHAT'S INCLUDED:

GAS HOT BOX ●
HEATLIE HB9000DS

GAS BOTTLE ●
9L LPG GAS BOTTLE

GAS REGULATOR STAND ●
REGULATES/REDUCES PRESSURE FROM THE
GAS BOTTLE TO THE APPLIANCE



SET-UP INSTRUCTIONS:

GAS BOTTLE AND LINE FITTINGS

1. Place gas bottle at the side or rear of the unit, out of the way.
2. Connect the regulator to the bottle. **Note:** This is a low-pressure appliance and a pressure regulator must be used.
3. Tighten gas bottle connection anti-clockwise. Keep the gas line away from potential hot surfaces.
4. **CONNECT** gas line from Hot Box to the regulator noting the grooves that the bayonet lines up with (example to right). Once inserted twist to lock the connection (Important)
5. **Leak Test:** With the gas line connected, turn gas on at bottle and check for leaks. Use soapy water and brush or spray over joints on gas bottle and connection at hotbox and watch for bubbles.



FEATURES

- 18 rack capacity (9 supplied with the item).
- Dimensions: 1930H x 750D x 710W.
- Shelves are 680mm x 535mm.
- Weight: 105kg
- Fuelled by LPG with a max temperature of 160C.
- Controlled thermostatically by an adjustable control knob.

LIGHTING/IGNITION

1. Burner to off position and open oven door.
2. Turn on valve at gas cylinder.
3. Turn on gas by pushing down knob and rotating to high (anti-clockwise). This also engages the flame failure. Continue to hold down knob.
4. Light immediately by pressing piezo igniter. If ignition does not occur release the knob and wait 30 seconds before trying again.
5. Once the burner is alight, continue to hold down the knob for a further 20 seconds, then release
6. After use turn off knob control and the valve at the gas cylinder.



NEED HELP?
CALL OUR OFFICE

8346 5545



OUT OF HOURS SUPPORT: 1300 161 024